


MODEL : GBV-202 | Bellow Seal Globe Valve



Connection : Flange PN 16, PN 40


DESCRIPTION

Design	: DIN 3356
Face to face	: DIN 3202
Flanges	: DIN 2501 DIN 2547 DIN 2526 FORM E BW TO DIN 3239
Testing	: DIN 3352 DIN 3230
Rating P - T	: DIN 2401
Suitable Medium	: W.O.G



MATERIAL LIST

No.	Parts	PN 16 Rating	PN 40 Rating
1	*Body	1.0619	Cast Steel GP240GH
2	*Seat Ring	X20Cr13	Stainless Steel X20Cr13
3	*Disc	X20Cr13	Stainless Steel X20Cr13
4	Gasket	S. S. Reinforced Graphite	Graphite - CrNiSt
5	Bellows	SS304 SS316L	SS304 SS316
6	*Gland	1.046	Forged Steel C 22.8
7	*Bonnet	1.0619	Cast Steel GP240GH
8	*Stem	X20Cr13	Stainless Steel X20Cr13
9	Handwheel	Steel	Cast Steel GP240GH



*Optional : SS304 | SS316

DIMENSIONS (mm)

SIZE	L	H	W		WEIGHT(Kg)		
			PN16 25	PN40	PN16	PN25	PN40
15	130	191	120	140	3.7	4.3	4.3
20	150	191	120	140	4.4	4.8	4.8
25	160	197	140	140	5.1	6.3	6.3
32	180	200	140	160	7.5	7.8	7.8
40	200	218	160	180	8.8	10.3	10.3
50	230	220	180	180	12.2	12.6	12.6
65	290	238	180	200	16.1	19	19
80	310	257	200	250	21.4	25	25
100	350	340	250	300	33	35	35
125	400	360	300	350	51	56	56
150	480	390	300	350	69	74	74
200	600	530	400	450	105	144	160
250	730	665	520	520	180	238	260
300	850	720	520	520	265	339	370

Specification is subject to change without prior notice